RENT4WORK

Technical datasheet
Document generated on November 23, 2026

CROWN

Crown FC 5245 3.0

Electric counterbalance · 3 t

Machine

Manufacturer	**Crown**
Model	**FC 5245 3.0**
Type	**Electric counterbalance**
Rated capacity	**3 t**
Operating weight	**4048 kg**

Basic dimensions

Load centre distance	**500 mm**
Seat height h7	**1251 mm**
Track width, front b10	**965 mm**
Length to face of forks l2	**2315 mm**
Wheelbase y	**1390 mm**
Ground clearance m1	**76 mm**
Turning radius Wa	**1975 mm**
Working aisle width Ast (800×1200 pallets)	**3786 mm**
Working aisle width Ast (1000×1200 pallets)	**3607 mm**
Load distance x	**410 mm**

Performance and mast

Travel speed, laden	**17,7 km/h**
Travel speed, unladen	**19,7 km/h**
Gradeability, laden	**8,5 %**
Gradeability, unladen	**14 %**

Battery and power supply

Battery voltage	**48 V**

Battery capacity	**945 Ah**

Axle loads

Front axle load, laden	**7269 kg**
Front axle load, unladen	**2132 kg**
Rear axle load, laden	**1093 kg**
Rear axle load, unladen	**3323 kg**

Data obtained from the manufacturers' datasheets.