RENT4WORK

Technical datasheet
Document generated on November 23, 2026

HYSTER

Hyster E1.6XN

Electric counterbalance · 1,6 t

Machine

Manufacturer	**Hyster**
Model	**E1.6XN**
Type	**Electric counterbalance**
Rated capacity	**1,6 t**
Lift height	**3,39 m**
Operating weight	**3414 kg**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3390 mm**
Height, mast lowered h1	**2180 mm**
Free lift h2	**100 mm**
Height, mast extended h4	**4006 mm**
Height of overhead guard h6	**2250 mm**
Seat height h7	**1161 mm**
Length to face of forks l2	**1908 mm**
Wheelbase y	**1220 mm**
Ground clearance m1	**87 mm**
Turning radius Wa	**1644 mm**
Working aisle width Ast (800×1200 pallets)	**3404 mm**
Working aisle width Ast (1000×1200 pallets)	**3216 mm**
Load distance x	**360 mm**

Performance and mast

Drive motor power	**18,4 kW**
Travel speed, laden	**18,4 km/h**

Travel speed, unladen	**18,4 km/h**

Battery and power supply

Battery voltage	**48 V**
Battery capacity	**690 Ah**

Axle loads

Front axle load, laden	**4233 kg**
Front axle load, unladen	**1506 kg**
Rear axle load, laden	**782 kg**
Rear axle load, unladen	**1908 kg**

Data obtained from the manufacturers' datasheets.