RENT4WORK

Technical datasheet
Document generated on November 23, 2026

HYSTER

Hyster E4.0XN

4 t

Machine

Manufacturer	**Hyster**
Model	**E4.0XN**
Rated capacity	**4 t**
Lift height	**3,00 m**
Operating weight	**7217 kg**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3000 mm**
Height, mast lowered h1	**2134 mm**
Free lift h2	**100 mm**
Height, mast extended h4	**3783 mm**
Height of overhead guard h6	**2388 mm**
Seat height h7	**1324 mm**
Length to face of forks l2	**2451 mm**
Wheelbase y	**1574 mm**
Ground clearance m1	**90 mm**
Turning radius Wa	**2165 mm**
Working aisle width Ast (800×1200 pallets)	**4012 mm**
Working aisle width Ast (1000×1200 pallets)	**3812 mm**
Load distance x	**447 mm**

Performance and mast

Drive motor power	**21 kW**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**3870 kg**
Max capacity at 3,000 mm (600 mm load centre)	**3520 kg**
Max capacity at 4,000 mm (500 mm load centre)	**3860 kg**
Max capacity at 4,000 mm (600 mm load centre)	**3500 kg**
Max capacity at 5,000 mm (500 mm load centre)	**3630 kg**
Max capacity at 5,000 mm (600 mm load centre)	**3310 kg**

Data obtained from the manufacturers' datasheets.