RENT4WORK

Technical datasheet
Document generated on November 23, 2026

HYUNDAI

Hyundai 30B-9

Electric · 3 t

Machine

Manufacturer	**Hyundai**
Model	**30B-9**
Rated capacity	**3 t**
Lift height	**3,00 m**
Power source	**Electric**
Operating weight	**4573 kg**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3005 mm**
Height, mast lowered h1	**2012 mm**
Free lift h2	**115 mm**
Height, mast extended h4	**4185 mm**
Seat height h7	**1275 mm**
Overall width b1	**1200 mm**
Track width, front b10	**993 mm**
Length to face of forks l2	**2503 mm**
Wheelbase y	**1600 mm**
Ground clearance m1	**117 mm**
Turning radius Wa	**2150 mm**
Working aisle width Ast (800×1200 pallets)	**4009 mm**
Working aisle width Ast (1000×1200 pallets)	**3829 mm**
Load distance x	**458 mm**

Performance and mast

Tyre type	**Solid resilient**

Travel speed, laden	**14 km/h**
Travel speed, unladen	**15 km/h**
Gradeability, laden	**17 %**
Gradeability, unladen	**17 %**

Battery and power supply

Battery voltage	**48 V**
Battery capacity	**660 Ah**

Axle loads

Front axle load, laden	**6630 kg**
Front axle load, unladen	**1834 kg**
Rear axle load, laden	**974 kg**
Rear axle load, unladen	**2770 kg**

Data obtained from the manufacturers' datasheets.