RENT4WORK

Technical datasheet
Document generated on November 23, 2026

JUNGHEINRICH

Jungheinrich ETV C20

Reach truck · 2 t

Machine

Manufacturer	**Jungheinrich**
Model	**ETV C20**
Type	**Reach truck**
Rated capacity	**2 t**
Lift height	**5,30 m**
Operating weight	**4010 kg**

Basic dimensions

Lift height h3	**5300 mm**
Height, mast lowered h1	**2400 mm**
Free lift h2	**1670 mm**
Height, mast extended h4	**6030 mm**
Height of overhead guard h6	**2290 mm**
Seat height h7	**1166 mm**
Overall width b1	**1409 mm**
Length to face of forks l2	**1360 mm**
Wheelbase y	**1520 mm**
Ground clearance m1	**80 mm**
Turning radius Wa	**1795 mm**
Working aisle width Ast (800×1200 pallets)	**2871 mm**
Working aisle width Ast (1000×1200 pallets)	**2829 mm**
Load distance x	**421 mm**

Performance and mast

Drive motor power	**7,5 kW**
Travel speed, laden	**11,8 km/h**

Travel speed, unladen	**12,2 km/h**
Gradeability, laden	**6 %**
Gradeability, unladen	**10 %**

Battery and power supply

Battery voltage	**48 V**
Battery capacity	**560 Ah**

Axle loads

Front axle load, unladen	**2410 kg**
Rear axle load, unladen	**1600 kg**

Data obtained from the manufacturers' datasheets.