RENT4WORK

**Technical datasheet**
Document generated on November 23, 2026

KALMAR

# Kalmar DCG600-15LB

Diesel counterbalance · 60 t

## Machine

| | |
|---|---|
| Manufacturer | **Kalmar** |
| Model | **DCG600-15LB** |
| Type | **Diesel counterbalance** |
| Rated capacity | **60 t** |
| Lift height | **4,00 m** |
| Operating weight | **88.500 kg** |

## Basic dimensions

| | |
|---|---|
| Load centre distance | **1500 mm** |
| Lift height h3 | **4000 mm** |
| Height, mast lowered h1 | **5750 mm** |
| Height, mast extended h4 | **7700 mm** |
| Height of overhead guard h6 | **4000 mm** |
| Seat height h7 | **3000 mm** |
| Overall width b1 | **4670 mm** |
| Length to face of forks l2 | **1615 mm** |
| Wheelbase y | **5750 mm** |
| Ground clearance m1 | **280 mm** |
| Turning radius Wa | **8000 mm** |
| Working aisle width Ast (800×1200 pallets) | **12215 mm** |

## Performance and mast

| | |
|---|---|
| Gradeability, laden | **24 %** |
| Gradeability, unladen | **44 %** |

## Axle loads

| | |
|---|---|
| Front axle load, laden | **139500 kg** |
| Front axle load, unladen | **47000 kg** |
| Rear axle load, laden | **10000 kg** |
| Rear axle load, unladen | **42500 kg** |

Data obtained from the manufacturers' datasheets.