RENT4WORK

Technical datasheet
Document generated on November 23, 2026

LINDE

Linde E 20

Electric counterbalance · Electric · 2 t

Machine

Manufacturer	**Linde**
Model	**E 20**
Type	**Electric counterbalance**
Rated capacity	**2 t**
Lift height	**3,03 m**
Power source	**Electric**
Operating weight	**4310 kg**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3030 mm**
Height, mast lowered h1	**2181 mm**
Free lift h2	**150 mm**
Height, mast extended h4	**3694 mm**
Height of overhead guard h6	**2165 mm**
Seat height h7	**1102 mm**
Track width, front b10	**972 mm**
Length to face of forks l2	**2320 mm**
Wheelbase y	**1652 mm**
Ground clearance m1	**122 mm**
Turning radius Wa	**1900 mm**
Working aisle width Ast (800×1200 pallets)	**3769 mm**
Working aisle width Ast (1000×1200 pallets)	**3642 mm**
Load distance x	**420 mm**

Performance and mast

FEM fork carriage class	**FEM 2A**
Tyre type	**Solid resilient**
Travel speed, laden	**20 km/h**
Travel speed, unladen	**20 km/h**
Gradeability, laden	**20,3 %**
Gradeability, unladen	**31,5 %**

Axle loads

Front axle load, laden	**5355 kg**
Front axle load, unladen	**2241 kg**
Rear axle load, laden	**955 kg**
Rear axle load, unladen	**2069 kg**

Data obtained from the manufacturers' datasheets.