RENT4WORK

Technical datasheet

Document generated on November 23, 2026

LINDE

Linde E100 1200

Electric counterbalance · Electric · 10 t

Machine

Manufacturer	**Linde**
Model	**E100 1200**
Type	**Electric counterbalance**
Rated capacity	**10 t**
Lift height	**4,00 m**
Power source	**Electric**
Operating weight	**24.062 kg**

Basic dimensions

Load centre distance	**1200 mm**
Lift height h3	**4000 mm**
Height, mast lowered h1	**3736 mm**
Free lift h2	**150 mm**
Height, mast extended h4	**5661 mm**
Height of overhead guard h6	**3150 mm**
Seat height h7	**2004 mm**
Track width, front b10	**1874 mm**
Length to face of forks l2	**4584 mm**
Wheelbase y	**3000 mm**
Ground clearance m1	**200 mm**
Turning radius Wa	**4102 mm**
Working aisle width Ast (800×1200 pallets)	**7586 mm**
Load distance x	**884 mm**

Performance and mast

Tyre type	**Pneumatic**

Travel speed, laden	**18 km/h**
Travel speed, unladen	**20 km/h**

Battery and power supply

Battery capacity	**930 Ah**

Axle loads

Front axle load, laden	**30317 kg**
Front axle load, unladen	**13370 kg**
Rear axle load, laden	**3745 kg**
Rear axle load, unladen	**10692 kg**

Data obtained from the manufacturers' datasheets.