RENT4WORK

**Technical datasheet**
Document generated on November 23, 2026

LINDE

# Linde E20 600H

Electric counterbalance · Electric · 2 t

## Machine

| | |
|---|---|
| Manufacturer | **Linde** |
| Model | **E20 600H** |
| Type | **Electric counterbalance** |
| Rated capacity | **2 t** |
| Lift height | **3,33 m** |
| Power source | **Electric** |
| Operating weight | **4897 kg** |

## Basic dimensions

| | |
|---|---|
| Load centre distance | **600 mm** |
| Lift height h3 | **3330 mm** |
| Height, mast lowered h1 | **2331 mm** |
| Free lift h2 | **150 mm** |
| Height, mast extended h4 | **3994 mm** |
| Height of overhead guard h6 | **2325 mm** |
| Seat height h7 | **1260 mm** |
| Track width, front b10 | **972 mm** |
| Length to face of forks l2 | **2354 mm** |
| Wheelbase y | **1686 mm** |
| Ground clearance m1 | **122 mm** |
| Turning radius Wa | **1934 mm** |
| Working aisle width Ast (800×1200 pallets) | **3803 mm** |
| Working aisle width Ast (1000×1200 pallets) | **3676 mm** |
| Load distance x | **420 mm** |

Performance and mast

| | |
|---|---|
| FEM fork carriage class | **FEM 2A** |
| Tyre type | **Solid resilient** |
| Travel speed, laden | **20 km/h** |
| Travel speed, unladen | **20 km/h** |
| Gradeability, laden | **18,4 %** |
| Gradeability, unladen | **27,3 %** |

## Axle loads

| | |
|---|---|
| Front axle load, laden | **5647 kg** |
| Front axle load, unladen | **2437 kg** |
| Rear axle load, laden | **1250 kg** |
| Rear axle load, unladen | **2460 kg** |

Data obtained from the manufacturers' datasheets.