RENT4WORK

Technical datasheet
Document generated on November 23, 2026

LINDE

Linde E30 600HL

Electric counterbalance · Electric · 3 t

Machine

Manufacturer	**Linde**
Model	**E30 600HL**
Type	**Electric counterbalance**
Rated capacity	**3 t**
Lift height	**3,29 m**
Power source	**Electric**
Operating weight	**5651 kg**

Basic dimensions

Load centre distance	**600 mm**
Lift height h3	**3295 mm**
Height, mast lowered h1	**2326 mm**
Free lift h2	**150 mm**
Height, mast extended h4	**4058 mm**
Height of overhead guard h6	**2325 mm**
Seat height h7	**1260 mm**
Track width, front b10	**996 mm**
Length to face of forks l2	**2533 mm**
Wheelbase y	**1831 mm**
Ground clearance m1	**118 mm**
Turning radius Wa	**2079 mm**
Working aisle width Ast (800×1200 pallets)	**3980 mm**
Working aisle width Ast (1000×1200 pallets)	**3851 mm**
Load distance x	**454 mm**

Performance and mast

FEM fork carriage class	**FEM 3A**
Tyre type	**Solid resilient**
Travel speed, laden	**20 km/h**
Travel speed, unladen	**20 km/h**
Gradeability, laden	**17,6 %**
Gradeability, unladen	**23,6 %**

Axle loads

Front axle load, laden	**7557 kg**
Front axle load, unladen	**2831 kg**
Rear axle load, laden	**1094 kg**
Rear axle load, unladen	**2820 kg**

Data obtained from the manufacturers' datasheets.