RENT4WORK

Technical datasheet
Document generated on November 23, 2026

LINDE

Linde E60 TRIPLEX

Electric counterbalance · Electric · 6 t

Machine

Manufacturer	**Linde**
Model	**E60 TRIPLEX**
Type	**Electric counterbalance**
Rated capacity	**6 t**
Lift height	**3,85 m**
Power source	**Electric**

Basic dimensions

Load centre distance	**600 mm**
Lift height h3	**3850 mm**
Height, mast lowered h1	**2890 mm**
Free lift h2	**150 mm**
Height, mast extended h4	**4754 mm**
Height of overhead guard h6	**2838 mm**
Seat height h7	**1705 mm**
Track width, front b10	**1326 mm**
Length to face of forks l2	**3493 mm**
Wheelbase y	**2300 mm**
Ground clearance m1	**228 mm**
Turning radius Wa	**3000 mm**
Working aisle width Ast (800×1200 pallets)	**5110 mm**
Working aisle width Ast (1000×1200 pallets)	**4910 mm**
Load distance x	**710 mm**

Performance and mast

FEM fork carriage class	**FEM 4A**

Tyre type	**Solid resilient**
Travel speed, laden	**20 km/h**
Travel speed, unladen	**20 km/h**
Gradeability, laden	**16,4 %**
Gradeability, unladen	**24,6 %**

Data obtained from the manufacturers' datasheets.