RENT4WORK

Technical datasheet
Document generated on November 23, 2026

LINDE

Linde E80 900

Electric counterbalance · Electric · 8 t

Machine

Manufacturer	**Linde**
Model	**E80 900**
Type	**Electric counterbalance**
Rated capacity	**8 t**
Lift height	**3,05 m**
Power source	**Electric**

Basic dimensions

Load centre distance	**900 mm**
Lift height h3	**3050 mm**
Height, mast lowered h1	**2885 mm**
Free lift h2	**150 mm**
Height, mast extended h4	**4447 mm**
Height of overhead guard h6	**2838 mm**
Seat height h7	**1705 mm**
Track width, front b10	**1564 mm**
Length to face of forks l2	**3733 mm**
Wheelbase y	**2400 mm**
Ground clearance m1	**220 mm**
Turning radius Wa	**3205 mm**
Working aisle width Ast (800×1200 pallets)	**5355 mm**
Working aisle width Ast (1000×1200 pallets)	**5155 mm**
Load distance x	**750 mm**

Performance and mast

FEM fork carriage class	**FEM 4A**

Tyre type	**Solid resilient**
Travel speed, laden	**20 km/h**
Travel speed, unladen	**20 km/h**
Gradeability, laden	**12,2 %**
Gradeability, unladen	**18,4 %**

Data obtained from the manufacturers' datasheets.