RENT4WORK

Technical datasheet
Document generated on November 23, 2026

MITSUBISHI

Mitsubishi FB20PNT

Electric counterbalance · 2 t

Machine

Manufacturer	**Mitsubishi**
Model	**FB20PNT**
Type	**Electric counterbalance**
Rated capacity	**2 t**
Lift height	**3,33 m**
Operating weight	**3520 kg**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3330 mm**
Height, mast lowered h1	**2125 mm**
Free lift h2	**120 mm**
Height, mast extended h4	**4548 mm**
Height of overhead guard h6	**2050 mm**
Seat height h7	**953 mm**
Overall width b1	**1090 mm**
Track width, front b10	**912 mm**
Length to face of forks l2	**1984 mm**
Wheelbase y	**1395 mm**
Ground clearance m1	**95 mm**
Turning radius Wa	**1595 mm**
Working aisle width Ast (800×1200 pallets)	**3127 mm**
Working aisle width Ast (1000×1200 pallets)	**3308 mm**
Load distance x	**389 mm**

Performance and mast

Travel speed, laden	**16 km/h**
Travel speed, unladen	**16 km/h**

Axle loads

Front axle load, laden	**4870 kg**
Front axle load, unladen	**1610 kg**
Rear axle load, laden	**560 kg**
Rear axle load, unladen	**1910 kg**

Data obtained from the manufacturers' datasheets.