RENT4WORK

Technical datasheet
Document generated on November 23, 2026

MITSUBISHI

Mitsubishi FB30AN

Electric · 3 t

Machine

Manufacturer	**Mitsubishi**
Model	**FB30AN**
Rated capacity	**3 t**
Lift height	**3,27 m**
Power source	**Electric**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3270 mm**
Height, mast lowered h1	**2165 mm**
Free lift h2	**100 mm**
Height, mast extended h4	**4325 mm**
Height of overhead guard h6	**2240 mm**
Seat height h7	**1130 mm**
Overall width b1	**1190 mm**
Track width, front b10	**950 mm**
Length to face of forks l2	**2558 mm**
Wheelbase y	**1730 mm**
Ground clearance m1	**115 mm**
Turning radius Wa	**2064 mm**
Working aisle width Ast (1000×1200 pallets)	**3830 mm**

Performance and mast

Tyre type	**Solid resilient**
Travel speed, laden	**20 km/h**
Travel speed, unladen	**20 km/h**

Gradeability, laden	**13 %**
Gradeability, unladen	**22 %**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**3000 kg**
Max capacity at 3,000 mm (600 mm load centre)	**2700 kg**
Max capacity at 4,000 mm (500 mm load centre)	**3000 kg**
Max capacity at 4,000 mm (600 mm load centre)	**2700 kg**
Max capacity at 5,000 mm (500 mm load centre)	**2900 kg**
Max capacity at 5,000 mm (600 mm load centre)	**2700 kg**
Max capacity at 6,000 mm (500 mm load centre)	**2625 kg**
Max capacity at 6,000 mm (600 mm load centre)	**2475 kg**

Data obtained from the manufacturers' datasheets.