RENT4WORK

Technical datasheet
Document generated on November 23, 2026

MITSUBISHI

Mitsubishi FB50CN

Electric · 4,99 t

Machine

Manufacturer	**Mitsubishi**
Model	**FB50CN**
Rated capacity	**4,99 t**
Lift height	**3,30 m**
Power source	**Electric**
Operating weight	**7991 kg**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3300 mm**
Free lift h2	**150 mm**
Height, mast extended h4	**4205 mm**
Height of overhead guard h6	**2340 mm**
Seat height h7	**1320 mm**
Overall width b1	**1450 mm**
Track width, front b10	**1154 mm**
Length to face of forks l2	**2825 mm**
Wheelbase y	**1946 mm**
Ground clearance m1	**150 mm**
Turning radius Wa	**2289 mm**
Working aisle width Ast (1000×1200 pallets)	**4125 mm**
Load distance x	**540 mm**

Performance and mast

FEM fork carriage class	**FEM 3A**
Tyre type	**Solid resilient**

Travel speed, laden	**18 km/h**
Travel speed, unladen	**20 km/h**
Gradeability, laden	**14 %**
Gradeability, unladen	**22 %**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**4000 kg**
Max capacity at 3,000 mm (600 mm load centre)	**4000 kg**
Max capacity at 4,000 mm (500 mm load centre)	**4000 kg**
Max capacity at 4,000 mm (600 mm load centre)	**4000 kg**
Max capacity at 5,000 mm (500 mm load centre)	**4000 kg**
Max capacity at 5,000 mm (600 mm load centre)	**3900 kg**
Max capacity at 6,000 mm (500 mm load centre)	**3900 kg**
Max capacity at 6,000 mm (600 mm load centre)	**3650 kg**

Battery and power supply

Battery voltage	**80 V**
Battery capacity	**775 Ah**

Data obtained from the manufacturers' datasheets.