RENT4WORK

Technical datasheet
Document generated on November 23, 2026

MITSUBISHI

Mitsubishi FB60NH

Electric counterbalance · Electric · 6 t

Machine

Manufacturer	**Mitsubishi**
Model	**FB60NH**
Type	**Electric counterbalance**
Rated capacity	**6 t**
Lift height	**3,40 m**
Power source	**Electric**
Operating weight	**10.260 kg**

Basic dimensions

Load centre distance	**600 mm**
Lift height h3	**3400 mm**
Height, mast lowered h1	**2680 mm**
Free lift h2	**100 mm**
Height, mast extended h4	**4370 mm**
Height of overhead guard h6	**2420 mm**
Seat height h7	**1330 mm**
Track width, front b10	**1380 mm**
Wheelbase y	**2250 mm**
Ground clearance m1	**180 mm**
Turning radius Wa	**2650 mm**
Working aisle width Ast (1000×1200 pallets)	**4610 mm**
Load distance x	**650 mm**

Performance and mast

Tyre type	**Solid resilient**
Travel speed, laden	**20 km/h**

Travel speed, unladen	**20 km/h**
Gradeability, laden	**14,7 %**
Gradeability, unladen	**23,7 %**

Axle loads

Front axle load, laden	**14523 kg**
Front axle load, unladen	**5190 kg**
Rear axle load, laden	**1737 kg**
Rear axle load, unladen	**5070 kg**

Data obtained from the manufacturers' datasheets.