RENT4WORK

Technical datasheet
Document generated on November 23, 2026

NOBLELIFT

Noblelift CBT15

Reach truck · Electric · 1,5 t

Machine

Manufacturer	**Noblelift**
Model	**CBT15**
Type	**Reach truck**
Rated capacity	**1,5 t**
Lift height	**6,20 m**
Power source	**Electric**
Operating weight	**4150 kg**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**6200 mm**
Height, mast lowered h1	**2575 mm**
Free lift h2	**2050 mm**
Height, mast extended h4	**7116 mm**
Height of overhead guard h6	**2260 mm**
Seat height h7	**260 mm**
Overall width b1	**1130 mm**
Track width, front b10	**952 mm**
Length to face of forks l2	**1700 mm**
Wheelbase y	**1158 mm**
Ground clearance m1	**50 mm**
Turning radius Wa	**1406 mm**
Working aisle width Ast (800×1200 pallets)	**3185 mm**
Working aisle width Ast (1000×1200 pallets)	**3060 mm**
Load distance x	**330 mm**

Performance and mast

FEM fork carriage class	**FEM 2A**
Tyre type	**Cushion**
Travel speed, laden	**11 km/h**
Travel speed, unladen	**11 km/h**

Battery and power supply

Battery voltage	**36 V**
Battery capacity	**700 Ah**

Data obtained from the manufacturers' datasheets.