RENT4WORK

Technical datasheet
Document generated on November 23, 2026

NOBLELIFT

Noblelift RT20ST2

Reach truck · 2 t

Machine

Manufacturer	**Noblelift**
Model	**RT20ST2**
Type	**Reach truck**
Rated capacity	**2 t**
Lift height	**7,00 m**
Operating weight	**3280 kg**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**7000 mm**
Height, mast lowered h1	**3068 mm**
Free lift h2	**2397 mm**
Height, mast extended h4	**7910 mm**
Height of overhead guard h6	**2260 mm**
Track width, front b10	**990 mm**
Length to face of forks l2	**1340 mm**
Wheelbase y	**1500 mm**
Ground clearance m1	**75 mm**
Turning radius Wa	**1770 mm**
Working aisle width Ast (800×1200 pallets)	**2880 mm**
Working aisle width Ast (1000×1200 pallets)	**2830 mm**

Performance and mast

Drive motor power	**5,5 kW**
Travel speed, laden	**9,5 km/h**
Travel speed, unladen	**9,5 km/h**

Gradeability, laden	**10 %**
Gradeability, unladen	**15 %**

Battery and power supply

Battery voltage	**48 V**
Battery capacity	**350 Ah**

Data obtained from the manufacturers' datasheets.