RENT4WORK

**Technical datasheet**
Document generated on November 23, 2026

NOBLELIFT

# Noblelift RT25ST2

Reach truck · 2,5 t

## Machine

| | |
|---|---|
| Manufacturer | **Noblelift** |
| Model | **RT25ST2** |
| Type | **Reach truck** |
| Rated capacity | **2,5 t** |
| Lift height | **7,00 m** |
| Operating weight | **3530 kg** |

## Basic dimensions

| | |
|---|---|
| Load centre distance | **500 mm** |
| Lift height h3 | **7000 mm** |
| Height, mast lowered h1 | **3068 mm** |
| Free lift h2 | **2397 mm** |
| Height, mast extended h4 | **7910 mm** |
| Height of overhead guard h6 | **2260 mm** |
| Track width, front b10 | **990 mm** |
| Length to face of forks l2 | **1400 mm** |
| Wheelbase y | **1650 mm** |
| Ground clearance m1 | **75 mm** |
| Turning radius Wa | **1885 mm** |
| Working aisle width Ast (800×1200 pallets) | **2950 mm** |
| Working aisle width Ast (1000×1200 pallets) | **2920 mm** |

## Performance and mast

| | |
|---|---|
| Drive motor power | **5,5 kW** |
| Travel speed, laden | **9,5 km/h** |
| Travel speed, unladen | **9,5 km/h** |

| | |
|---|---|
| Gradeability, laden | **10 %** |
| Gradeability, unladen | **15 %** |

## Battery and power supply

| | |
|---|---|
| Battery voltage | **48 V** |
| Battery capacity | **420 Ah** |

Data obtained from the manufacturers' datasheets.