RENT4WORK

**Technical datasheet**
Document generated on November 23, 2026

STILL

# STILL FM 4 W 25

Reach truck · 2,5 t

## Machine

| | |
|---|---|
| Manufacturer | **STILL** |
| Model | **FM 4 W 25** |
| Type | **Reach truck** |
| Rated capacity | **2,5 t** |
| Lift height | **9,65 m** |

## Basic dimensions

| | |
|---|---|
| Load centre distance | **600 mm** |
| Lift height h3 | **9650 mm** |
| Height, mast lowered h1 | **4083 mm** |
| Free lift h2 | **3353 mm** |
| Height, mast extended h4 | **10400 mm** |
| Height of overhead guard h6 | **2215 mm** |
| Seat height h7 | **1087 mm** |
| Wheelbase y | **1665 mm** |
| Ground clearance m1 | **81 mm** |
| Turning radius Wa | **1932 mm** |

## Performance and mast

| | |
|---|---|
| Tyre type | **Polyurethane** |
| Drive motor power | **7,2 kW** |
| Travel speed, laden | **13 km/h** |
| Travel speed, unladen | **13 km/h** |
| Gradeability, laden | **9 %** |
| Gradeability, unladen | **14 %** |

Battery and power supply

| | |
|---|---|
| Battery voltage | **48 V** |
| Battery capacity | **620 Ah** |

## Axle loads

| | |
|---|---|
| Front axle load, unladen | **2880 kg** |
| Rear axle load, unladen | **2080 kg** |

Data obtained from the manufacturers' datasheets.