RENT4WORK

Technical datasheet
Document generated on November 23, 2026

STILL

STILL R 60-25 L (1995-2005)

Electric counterbalance · Electric · 2,5 t

INDICATIVE NEW PRICE
€32,500

IEQ INDEX
0.58

Indicative new price: Indicative estimate of this model's price when new, reconstructed from market data: it is not the manufacturer's official list price.

What the IEQ index is: The IEQ (Height Efficiency Index) shows how much of its rated capacity the machine keeps when working at high lift heights. The closer the value is to 1, the less the capacity drops as the mast extends. With a low index, at height you will be able to handle loads noticeably lighter than the rated capacity suggests.

Machine

Manufacturer	**STILL**
Model	**R 60-25 L (1995-2005)**
Type	**Electric counterbalance**
Rated capacity	**2,5 t**
Lift height	**3,22 m**
Power source	**Electric**
Operating weight	**4772 kg**
Commercial status	**Used, discontinued**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3220 mm**
Height, mast lowered h1	**2250 mm**
Free lift h2	**160 mm**
Height, mast extended h4	**3880 mm**
Height of overhead guard h6	**2250 mm**
Seat height h7	**1070 mm**
Overall width b1	**1192 mm**
Track width, front b10	**945 mm**

Length to face of forks l2	**2406 mm**
Wheelbase y	**1679 mm**
Ground clearance m1	**100 mm**
Turning radius Wa	**2130 mm**
Working aisle width Ast (800×1200 pallets)	**3945 mm**
Working aisle width Ast (1000×1200 pallets)	**3780 mm**
Load distance x	**395 mm**

Performance and mast

Residual capacity at maximum lift height	**1250 kg**
Mast type	**Standard**
FEM fork carriage class	**FEM 2**
Tyre type	**Solid resilient**
Drive motor power	**12,5 kW**
Travel speed, laden	**16 km/h**
Travel speed, unladen	**16 km/h**
Gradeability, laden	**8 %**
Gradeability, unladen	**13 %**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**2500 kg**
Max capacity at 3,000 mm (600 mm load centre)	**2250 kg**
Max capacity at 4,000 mm (500 mm load centre)	**2150 kg**
Max capacity at 4,000 mm (600 mm load centre)	**1850 kg**
Max capacity at 5,000 mm (500 mm load centre)	**1750 kg**
Max capacity at 5,000 mm (600 mm load centre)	**1450 kg**
Max capacity at 6,000 mm (500 mm load centre)	**1250 kg**
Max capacity at 6,000 mm (600 mm load centre)	**1000 kg**

Battery and power supply

Battery technology	**Lead-acid**
Battery voltage	**80 V**
Battery capacity	**620 Ah**

Battery charger power	**6,2 kW**
Energy per charging cycle	**59,5 kWh**

Axle loads

Front axle load, laden	**6185 kg**
Front axle load, unladen	**2322 kg**
Rear axle load, laden	**1087 kg**
Rear axle load, unladen	**2450 kg**

Data obtained from the manufacturers' datasheets.