RENT4WORK

Technical datasheet
Document generated on November 23, 2026

STILL

STILL RCE 25 (2023+)

Electric counterbalance · Electric · 2,5 t

INDICATIVE NEW PRICE
€28,500

IEQ INDEX
0.56

Indicative new price: Indicative estimate of this model's price when new, reconstructed from market data: it is not the manufacturer's official list price.

What the IEQ index is: The IEQ (Height Efficiency Index) shows how much of its rated capacity the machine keeps when working at high lift heights. The closer the value is to 1, the less the capacity drops as the mast extends. With a low index, at height you will be able to handle loads noticeably lighter than the rated capacity suggests.

Machine

Manufacturer	**STILL**
Model	**RCE 25 (2023+)**
Type	**Electric counterbalance**
Rated capacity	**2,5 t**
Lift height	**3,00 m**
Power source	**Electric**
Operating weight	**4202 kg**
Commercial status	**New, in production**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3000 mm**
Height, mast lowered h1	**2137 mm**
Free lift h2	**150 mm**
Height, mast extended h4	**3995 mm**
Height of overhead guard h6	**2150 mm**
Seat height h7	**1167 mm**
Overall width b1	**1265 mm**
Track width, front b10	**1040 mm**

Length to face of forks l2	**2420 mm**
Wheelbase y	**1545 mm**
Ground clearance m1	**102 mm**
Turning radius Wa	**2096 mm**
Working aisle width Ast (800×1200 pallets)	**3960 mm**
Working aisle width Ast (1000×1200 pallets)	**3760 mm**
Load distance x	**415 mm**

Performance and mast

Residual capacity at maximum lift height	**1150 kg**
Mast type	**Standard**
FEM fork carriage class	**FEM 2**
Tyre type	**Solid resilient**
Drive motor power	**10,2 kW**
Travel speed, laden	**15 km/h**
Travel speed, unladen	**15 km/h**
Gradeability, laden	**7,7 %**
Gradeability, unladen	**18 %**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**2500 kg**
Max capacity at 3,000 mm (600 mm load centre)	**2150 kg**
Max capacity at 4,000 mm (500 mm load centre)	**2100 kg**
Max capacity at 4,000 mm (600 mm load centre)	**1800 kg**
Max capacity at 5,000 mm (500 mm load centre)	**1650 kg**
Max capacity at 5,000 mm (600 mm load centre)	**1400 kg**
Max capacity at 6,000 mm (500 mm load centre)	**1150 kg**
Max capacity at 6,000 mm (600 mm load centre)	**950 kg**

Battery and power supply

Battery technology	**Lead-acid**
Battery voltage	**80 V**
Battery capacity	**360 Ah**

Battery charger power	**3,6 kW**
Energy per charging cycle	**34,6 kWh**

Axle loads

Front axle load, laden	**5890 kg**
Front axle load, unladen	**1792 kg**
Rear axle load, laden	**812 kg**
Rear axle load, unladen	**2410 kg**

Data obtained from the manufacturers' datasheets.