RENT4WORK

Technical datasheet
Document generated on November 23, 2026

STILL

STILL RX 20-14 (Serie 1) (2005-2017)

Electric counterbalance · Electric · 1,4 t

INDICATIVE NEW PRICE
€25,000

IEQ INDEX
0.60

Indicative new price: Indicative estimate of this model's price when new, reconstructed from market data: it is not the manufacturer's official list price.

What the IEQ index is: The IEQ (Height Efficiency Index) shows how much of its rated capacity the machine keeps when working at high lift heights. The closer the value is to 1, the less the capacity drops as the mast extends. With a low index, at height you will be able to handle loads noticeably lighter than the rated capacity suggests.

Machine

Manufacturer	**STILL**
Model	**RX 20-14 (Serie 1) (2005-2017)**
Type	**Electric counterbalance**
Rated capacity	**1,4 t**
Lift height	**4,32 m**
Power source	**Electric**
Operating weight	**2720 kg**
Commercial status	**Used, discontinued**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**4320 mm**
Height, mast lowered h1	**1960 mm**
Free lift h2	**1380 mm**
Height, mast extended h4	**4920 mm**
Height of overhead guard h6	**2082 mm**
Seat height h7	**1015 mm**
Overall width b1	**1099 mm**
Track width, front b10	**932 mm**

Length to face of forks l2	**2001 mm**
Wheelbase y	**1321 mm**
Ground clearance m1	**90 mm**
Turning radius Wa	**1525 mm**
Working aisle width Ast (800×1200 pallets)	**3355 mm**
Working aisle width Ast (1000×1200 pallets)	**3231 mm**
Load distance x	**351 mm**

Performance and mast

Residual capacity at maximum lift height	**1020 kg**
Mast type	**Standard**
FEM fork carriage class	**FEM 2**
Tyre type	**Solid resilient**
Drive motor power	**2x4.3 kW**
Travel speed, laden	**16 km/h**
Travel speed, unladen	**16 km/h**
Gradeability, laden	**14,5 %**
Gradeability, unladen	**20 %**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**1400 kg**
Max capacity at 3,000 mm (600 mm load centre)	**1160 kg**
Max capacity at 4,000 mm (500 mm load centre)	**1250 kg**
Max capacity at 4,000 mm (600 mm load centre)	**1040 kg**
Max capacity at 5,000 mm (500 mm load centre)	**1020 kg**
Max capacity at 5,000 mm (600 mm load centre)	**850 kg**
Max capacity at 6,000 mm (500 mm load centre)	**780 kg**
Max capacity at 6,000 mm (600 mm load centre)	**650 kg**

Battery and power supply

Battery technology	**Lead-acid**
Battery voltage	**48 V**
Battery capacity	**500 Ah**

Battery charger power	**3,6 kW**
Energy per charging cycle	**28,8 kWh**

Axle loads

Front axle load, laden	**3580 kg**
Front axle load, unladen	**1260 kg**
Rear axle load, laden	**540 kg**
Rear axle load, unladen	**1460 kg**

Data obtained from the manufacturers' datasheets.