RENT4WORK

Technical datasheet
Document generated on November 23, 2026

STILL

STILL RX 20-20 PL (2018+)

Electric counterbalance · Electric · 2 t

INDICATIVE NEW PRICE
€35,500

IEQ INDEX
0.69

Indicative new price: Indicative estimate of this model's price when new, reconstructed from market data: it is not the manufacturer's official list price.

What the IEQ index is: The IEQ (Height Efficiency Index) shows how much of its rated capacity the machine keeps when working at high lift heights. The closer the value is to 1, the less the capacity drops as the mast extends. With a low index, at height you will be able to handle loads noticeably lighter than the rated capacity suggests.

Machine

Manufacturer	**STILL**
Model	**RX 20-20 PL (2018+)**
Type	**Electric counterbalance**
Rated capacity	**2 t**
Lift height	**3,18 m**
Power source	**Electric**
Operating weight	**3486 kg**
Commercial status	**New, in production**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3180 mm**
Height, mast lowered h1	**2160 mm**
Free lift h2	**150 mm**
Height, mast extended h4	**3742 mm**
Height of overhead guard h6	**2035 mm**
Seat height h7	**1058 mm**
Overall width b1	**1149 mm**
Track width, front b10	**942 mm**

Length to face of forks l2	**2066 mm**
Wheelbase y	**1517 mm**
Ground clearance m1	**≥90**
Turning radius Wa	**1678 mm**
Working aisle width Ast (800×1200 pallets)	**3502 mm**
Working aisle width Ast (1000×1200 pallets)	**3377 mm**
Load distance x	**374 mm**

Performance and mast

Residual capacity at maximum lift height	**1520 kg**
Mast type	**Standard**
FEM fork carriage class	**FEM 2**
Tyre type	**Solid resilient**
Drive motor power	**2 x 6,5 kW**
Travel speed, laden	**16 km/h**
Travel speed, unladen	**16 km/h**
Gradeability, laden	**20,4 %**
Gradeability, unladen	**30,3 %**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**2000 kg**
Max capacity at 3,000 mm (600 mm load centre)	**1820 kg**
Max capacity at 4,000 mm (500 mm load centre)	**1850 kg**
Max capacity at 4,000 mm (600 mm load centre)	**1680 kg**
Max capacity at 5,000 mm (500 mm load centre)	**1520 kg**
Max capacity at 5,000 mm (600 mm load centre)	**1380 kg**
Max capacity at 6,000 mm (500 mm load centre)	**1180 kg**
Max capacity at 6,000 mm (600 mm load centre)	**1070 kg**

Battery and power supply

Battery technology	**Lead-acid**
Battery voltage	**48 V**
Battery capacity	**625 Ah**

Battery charger power	**3,8 kW**
Energy per charging cycle	**36 kWh**

Axle loads

Front axle load, laden	**4860 kg**
Front axle load, unladen	**1689 kg**
Rear axle load, laden	**623 kg**
Rear axle load, unladen	**1794 kg**

Data obtained from the manufacturers' datasheets.