RENT4WORK

Technical datasheet
Document generated on November 23, 2026

STILL

STILL RX 60-25 (Serie 1) (2007-2017)

Electric counterbalance · Electric · 2,5 t

INDICATIVE NEW PRICE
€35,000

IEQ INDEX
0.60

Indicative new price: Indicative estimate of this model's price when new, reconstructed from market data: it is not the manufacturer's official list price.

What the IEQ index is: The IEQ (Height Efficiency Index) shows how much of its rated capacity the machine keeps when working at high lift heights. The closer the value is to 1, the less the capacity drops as the mast extends. With a low index, at height you will be able to handle loads noticeably lighter than the rated capacity suggests.

Machine

Manufacturer	**STILL**
Model	**RX 60-25 (Serie 1) (2007-2017)**
Type	**Electric counterbalance**
Rated capacity	**2,5 t**
Lift height	**3,02 m**
Power source	**Electric**
Operating weight	**4585 kg**
Commercial status	**Used, discontinued**

Basic dimensions

Load centre distance	**600 mm**
Lift height h3	**3020 mm**
Height, mast extended h4	**3650 mm**
Height of overhead guard h6	**2210 mm**
Overall width b1	**1199 mm**
Length to face of forks l2	**3353 mm**
Turning radius Wa	**2185 mm**
Load distance x	**383 mm**

Performance and mast

Residual capacity at maximum lift height	**1600 kg**
Mast type	**Standard**
FEM fork carriage class	**FEM 2**
Tyre type	**Solid resilient**
Travel speed, laden	**20 km/h**
Travel speed, unladen	**20 km/h**
Gradeability, laden	**25,5 %**
Gradeability, unladen	**29,7 %**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**2500 kg**
Max capacity at 3,000 mm (600 mm load centre)	**2310 kg**
Max capacity at 4,000 mm (500 mm load centre)	**2500 kg**
Max capacity at 4,000 mm (600 mm load centre)	**1900 kg**
Max capacity at 5,000 mm (500 mm load centre)	**2050 kg**
Max capacity at 5,000 mm (600 mm load centre)	**1500 kg**
Max capacity at 6,000 mm (500 mm load centre)	**1600 kg**
Max capacity at 6,000 mm (600 mm load centre)	**1150 kg**

Battery and power supply

Battery technology	**Lead-acid**
Battery voltage	**80 V**
Battery charger power	**0 kW**
Energy per charging cycle	**0 kWh**

Data obtained from the manufacturers' datasheets.