RENT4WORK

Technical datasheet
Document generated on November 23, 2026

STILL

STILL SXV-CB 10 (2008-2018)

Electric counterbalance · Electric · 1 t

INDICATIVE NEW PRICE
€19,000

IEQ INDEX
0.60

Indicative new price: Indicative estimate of this model's price when new, reconstructed from market data: it is not the manufacturer's official list price.

What the IEQ index is: The IEQ (Height Efficiency Index) shows how much of its rated capacity the machine keeps when working at high lift heights. The closer the value is to 1, the less the capacity drops as the mast extends. With a low index, at height you will be able to handle loads noticeably lighter than the rated capacity suggests.

Machine

Manufacturer	**STILL**
Model	**SXV-CB 10 (2008-2018)**
Type	**Electric counterbalance**
Rated capacity	**1 t**
Lift height	**5,38 m**
Power source	**Electric**
Operating weight	**2590 kg**
Commercial status	**Used, discontinued**

Basic dimensions

Load centre distance	**600 mm**
Lift height h3	**5380 mm**
Height, mast lowered h1	**1990 mm**
Height, mast extended h4	**6040 mm**
Height of overhead guard h6	**2190 mm**
Overall width b1	**828 mm**
Length to face of forks l2	**1454 mm**
Turning radius Wa	**1320 mm**
Working aisle width Ast (800×1200 pallets)	**2958 mm**

Load distance x	**195 mm**

Performance and mast

Residual capacity at maximum lift height	**550 kg**
Mast type	**Standard**
FEM fork carriage class	**FEM 2**
Tyre type	**Solid resilient**
Travel speed, laden	**8 km/h**
Travel speed, unladen	**12 km/h**
Gradeability, laden	**8 %**
Gradeability, unladen	**15 %**

Residual capacities and load chart

Max capacity at 3,000 mm (500 mm load centre)	**1000 kg**
Max capacity at 3,000 mm (600 mm load centre)	**850 kg**
Max capacity at 4,000 mm (500 mm load centre)	**900 kg**
Max capacity at 4,000 mm (600 mm load centre)	**750 kg**
Max capacity at 5,000 mm (500 mm load centre)	**750 kg**
Max capacity at 5,000 mm (600 mm load centre)	**600 kg**
Max capacity at 6,000 mm (500 mm load centre)	**550 kg**
Max capacity at 6,000 mm (600 mm load centre)	**450 kg**

Battery and power supply

Battery technology	**Lead-acid**
Battery voltage	**24 V**
Battery capacity	**300 Ah**
Battery charger power	**0,9 kW**
Energy per charging cycle	**8,6 kWh**

Data obtained from the manufacturers' datasheets.