RENT4WORK

Technical datasheet
Document generated on November 23, 2026

TOYOTA

Toyota 05-8FBM20T

Electric counterbalance · Electric · 2 t

Machine

Manufacturer	**Toyota**
Model	**05-8FBM20T**
Type	**Electric counterbalance**
Rated capacity	**2 t**
Lift height	**3,30 m**
Power source	**Electric**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3300 mm**
Height, mast lowered h1	**2120 mm**
Free lift h2	**115 mm**
Height, mast extended h4	**3870 mm**
Height of overhead guard h6	**2055 mm**
Seat height h7	**1059 mm**
Overall width b1	**1152 mm**
Track width, front b10	**925 mm**
Length to face of forks l2	**2122 mm**
Wheelbase y	**1561 mm**
Ground clearance m1	**90 mm**
Turning radius Wa	**1811 mm**
Working aisle width Ast (800×1200 pallets)	**3568 mm**
Working aisle width Ast (1000×1200 pallets)	**3438 mm**
Load distance x	**317 mm**

Performance and mast

Tyre type	**Solid resilient**
Drive motor power	**6 kW**
Travel speed, laden	**20 km/h**
Travel speed, unladen	**20 km/h**

Battery and power supply

Battery voltage	**48 V**
Battery capacity	**660 Ah**

Data obtained from the manufacturers' datasheets.