RENT4WORK

Technical datasheet
Document generated on November 23, 2026

TOYOTA

Toyota 05-9FBH30T

Electric counterbalance · Electric · 3 t

Machine

Manufacturer	**Toyota**
Model	**05-9FBH30T**
Type	**Electric counterbalance**
Rated capacity	**3 t**
Lift height	**3,30 m**
Power source	**Electric**
Operating weight	**5651 kg**

Basic dimensions

Load centre distance	**600 mm**
Lift height h3	**3300 mm**
Height, mast lowered h1	**2355 mm**
Free lift h2	**125 mm**
Height, mast extended h4	**3950 mm**
Height of overhead guard h6	**2215 mm**
Seat height h7	**1230 mm**
Overall width b1	**1195 mm**
Track width, front b10	**946 mm**
Length to face of forks l2	**2481 mm**
Wheelbase y	**1735 mm**
Ground clearance m1	**95 mm**
Turning radius Wa	**2200 mm**
Working aisle width Ast (800×1200 pallets)	**4033 mm**
Working aisle width Ast (1000×1200 pallets)	**3834 mm**
Load distance x	**440 mm**

Performance and mast

Tyre type	**Solid resilient**

Residual capacities and load chart

Max capacity at 3,000 mm (600 mm load centre)	**3000 kg**
Max capacity at 4,000 mm (600 mm load centre)	**3000 kg**
Max capacity at 5,000 mm (600 mm load centre)	**3000 kg**
Max capacity at 6,000 mm (600 mm load centre)	**2850 kg**

Battery and power supply

Battery voltage	**80 V**
Battery capacity	**700 Ah**

Axle loads

Front axle load, laden	**7491 kg**
Front axle load, unladen	**2705 kg**
Rear axle load, laden	**1160 kg**
Rear axle load, unladen	**2946 kg**

Data obtained from the manufacturers' datasheets.