RENT4WORK

Technical datasheet
Document generated on November 23, 2026

YALE

Yale ERP20UX

Electric counterbalance · 2 t

Machine

Manufacturer	**Yale**
Model	**ERP20UX**
Type	**Electric counterbalance**
Rated capacity	**2 t**
Operating weight	**4040 kg**

Basic dimensions

Height, mast lowered h1	**2015 mm**
Free lift h2	**140 mm**
Height of overhead guard h6	**2152 mm**
Overall width b1	**1285 mm**
Track width, front b10	**1058 mm**
Length to face of forks l2	**2302 mm**
Wheelbase y	**1485 mm**
Ground clearance m1	**65 mm**
Turning radius Wa	**2155 mm**
Working aisle width Ast (800×1200 pallets)	**4009 mm**
Working aisle width Ast (1000×1200 pallets)	**3879 mm**
Load distance x	**454 mm**

Performance and mast

Drive motor power	**8,5 kW**
Travel speed, laden	**15,7 km/h**
Travel speed, unladen	**15,7 km/h**

Axle loads

Front axle load, laden	**5110 kg**
Front axle load, unladen	**1770 kg**
Rear axle load, laden	**930 kg**
Rear axle load, unladen	**2270 kg**

Data obtained from the manufacturers' datasheets.