RENT4WORK

Technical datasheet
Document generated on November 23, 2026

YALE

Yale FB25RZ

2,5 t

Machine

Manufacturer	**Yale**
Model	**FB25RZ**
Rated capacity	**2,5 t**
Lift height	**3,01 m**

Basic dimensions

Load centre distance	**500 mm**
Lift height h3	**3010 mm**
Height, mast lowered h1	**1995 mm**
Free lift h2	**113 mm**
Height, mast extended h4	**3650 mm**
Height of overhead guard h6	**2119 mm**
Seat height h7	**1162 mm**
Length to face of forks l2	**2419 mm**
Wheelbase y	**1550 mm**
Ground clearance m1	**85 mm**
Turning radius Wa	**2068 mm**
Working aisle width Ast (800×1200 pallets)	**3557 mm**
Working aisle width Ast (1000×1200 pallets)	**3557 mm**
Load distance x	**463 mm**

Performance and mast

FEM fork carriage class	**FEM 2A**
Drive motor power	**8,3 kW**
Travel speed, laden	**13,6 km/h**
Travel speed, unladen	**15,2 km/h**

Gradeability, laden	**5,4 %**
Gradeability, unladen	**8,8 %**

Axle loads

Front axle load, laden	**5811 kg**
Front axle load, unladen	**1757 kg**
Rear axle load, laden	**744 kg**
Rear axle load, unladen	**2298 kg**

Data obtained from the manufacturers' datasheets.